



Silicone- and solvent-free emulsion based sealant for sealing and joining of parquet, cork, laminate as well as wooden floors. There are no harmful emissions. Woodflex is therefore environmentally friendly.

6 different suitable wood colours available. Application with standard caulking guns.

The sealant shows excellent adhesion, is fast drying, and may be sanded and painted. Generally it shows good adhesion without the use of primer on most building substrates like concrete, varnished wood, aluminium and hard-plastics.

Limitations / handling:

- not suitable for PE, PTFE and bitumen
- paintable

Technical data:

skin over time	climate 23/50	10 - 20 min
sealable after	climate 23/50	4 - 6 h
sandable after	climate 23/50	18 – 24 h
strengthenable	climate 23/50	2 –3 days
application temperature		+5°C / +40°C
temperature resistance	DIN 52455 T1	-25°C / +75°C
storage temperature		+5°C / +25°C
movement intake / elasticity		app. 7,5 %
density	DIN 52451	1,72 g/cm ³
shore A-hardness		70 - 80
shelf life unopened	cool and dry	12 months

colours available:

Packing

- 1 carton = 12 cartridges
- 1 pallet = 1344 cartridges
- 1 cartridge = 300 ml

Oak	CAW667505018	Cherry	CAW667505070
Beech	CAW667505060	Meranti	CAW667505071
pine	CAW667505063	Imbuia	CAW667505072